

Clean Version of Pending Claims

GTL + DRIVER

Applicant: Rodney Ruesch

Serial No.: 09/620,679

7. [AMENDED] A method of communicating data in an integrated circuit using internal interconnects, the method comprising:

receiving a data signal;

adjusting a first resistance coupled to a first supply voltage, based on a manufacturing process, the first supply voltage and a temperature;

adjusting a second resistance coupled to a second supply voltage, based on the manufacturing process, the first supply voltage and the temperature; and

adjusting a third resistance coupled to the second supply voltage, based on the manufacturing process, the first supply voltage and the temperature; and

wherein the first resistance, second resistance and third resistance are each individually adjustable.

8. A method of communicating data in an integrated circuit using internal interconnects, the method comprising:

selecting a resistance of a divider network based on a manufacturing process, a supply voltage and a temperature;

selecting an edge rate of a driver coupled to the divider network, the selected edge rate based on the manufacturing process, the supply voltage and the temperature;

receiving a data signal; and

providing an output based on the data signal, the resistance, and the edge rate.

9. The method of claim 8 wherein selecting an edge rate of a driver coupled to the divider network comprises maintaining a substantially constant edge rate.

10. The method of claim 8 wherein providing an output comprises turning on a PFET transistor and turning off an NFET transistor.
11. The method of claim 8 wherein selecting a resistance of a divider network comprises selecting a plurality of parallel resistance elements.
12. The method of claim 8 wherein selecting a resistance of a divider network comprises executing programming for selecting resistance elements from a plurality of switchable resistance elements.
13. The method of claim 8 wherein selecting an edge rate of a driver coupled to the divider network comprises selecting a plurality of parallel resistance elements.
14. The method of claim 8 wherein selecting an edge rate of a driver coupled to the divider network comprises executing programming for selecting resistance elements from a plurality of switchable resistance elements.
15. The method of claim 8 further comprising:
receiving a tristate enable signal; and
actuating a switchable resistance element in response to the tristate enable signal.
16. The method of claim 15 wherein actuating a switchable resistance element comprises actuating a programmable inverter.
23. The method of claim 7 wherein adjusting a first resistance includes changing a resistance of a semiconductor.
24. The method of claim 7 wherein adjusting a first resistance includes changing a gate voltage on a field effect transistor (FET).

25. The method of claim 7 wherein adjusting a first resistance includes selecting a predetermined number of programmable bits from a plurality of programmable bits.